

Ultra Series Multi-target Auto Tracking Panoramic PTZ Camera



Functions:

- 1/1.8" Progressive Scan 2MP CMOS
- 5.5~180mm, 33x Optical Zoom
- Fixed Lens:3.6mm/10mm
- Positioning Accuracy: 0.05°
- Starlight technology
- IR distance up to 200m.
- IP66

System Function	
Intelligent Identification	Facial Capture
Facial Detection Range	70m
Auto Tracking	Support
Multiple Targets Tracking	Support, Up To 30 Targets In One Second
Smart Detection	People And Facial Are Recognized Automatically.
Panoramic Camera	
Image Sensor	1/1.8" Progressive Scan Cmos
Day/night	ICR
Min. Illumination	Color: 0.001 Lux@(f1.2, Agc On), B/w: 0.0001 Lux@(f1.2, Agc On)
S/N Ratio	>55 dB
Smart Image Enhancement	WDR, Defog, HLC, BLC, HLC
DNR	Support
Horizontal Fov	106°
Vertical Fov	58°
Smart Detection	Motion Detection, People Detection
Video Compression	H.265/H.264/Mjpeg
Lens	3.6mm
Tracking PTZ Camera	
Image Sensor	1/1.8" Progressive Scan CMOS
Effective Pixels	1920x1080
Minimum Illumination	Color: 0.001 Lux@(f1.2, Agc On), B/w: 0.0001 Lux@(f1.2, Agc On)
Shutter Time	1/1~1/ 30000s
S/N Ratio	>55 dB
Day/Night	ICR

Ultra Series | SD6C233-H-0360

Optical Zoom	5.5~180mm,33x Optical Zoom
Horizontal Fov	66.31°~3.72°(wide-tele)
Aperture Range	F1.5 To F4.8
PTZ	
Pan Range	360°endless
Pan Speed	0.05° -300°/s
Tilt Range	-15°~90°(auto Flip)
Tilt Speed	0.05° -200°/s
Proportional Zoom	Rotation Speed Can Be Adjusted Automatically According To Zoom Multiples
Number Of Preset	256
Patrol	6 Patrols, Up To 16 Presets Per Patrol
Pattern	4 Patterns, With The Recording Time Not Less Than 10 Minutes Per Pattern
Trace Function	
Application Scene	Facial Capture And Uploading
Precautionary Area	6 Areas
Monitoring Area	70meters
Network	
API	Open-ended, Support Onvif, Support Hikvision Sdk And Third-party Management Platform
Protocols	Ipv4, Http, Ftp, Rtsp,dns, Ntp, Rtp, Tcp,udp, Igmp, Icmp, Arp
Infrared	
IR distance	200m
Ir Irradiation Angle	Adjustable By Zoom
Port	
Audio I/O	1 input,1 output(optical)
Alarm I/O	1 input,1 output(optical)
General	
Power Supply	24VAC
Power Consumption	Max.: 55 W
Working Temperature	Temperature: Outdoor: -40°C To 70°C (-40°F To 158°F)
Working Humidity	Humidity: ≤90%
Protection Level	IP66 Standard
Material	Aluminum Alloy
Weight (approx.)	Approx. 7.5KG

Accessories

Included:



Mount Adapter



AC24V/5A Power Adapter

Optional:



Wall Mount Bracket

Dimensions

